

# Ultra Premium

## Prepcoat Ultralock®

Product Base Code: UPUL

	Product Description	
	<p>Haymes Paint Ultralock® is a multi-function quick-drying, oil-based primer, sealer and undercoat. Use for priming bare surfaces, or as an undercoat on surfaces previously painted with either oil-based or water-based paints. It effectively seals stains, preventing them from penetrating new coatings. Easy to sand, Ultralock® delivers superior adhesion and is suitable for both interior and exterior use.</p>	
 Interior & Exterior	Key Features & Benefits	
	<b>Quick-drying</b>	Get the job done faster, you can apply 2 coats in one day.
	<b>Superior adhesion</b>	Bond to a wide range of surfaces with minimal preparation.
	<b>Stain sealer</b>	Seals common household stains
<b>Multi-function</b>	Suitable for use as a primer and undercoat on a wide variety of interior & exterior surfaces.	
 Mineral Turpentine wash-up	 Coverage Up to 16 sqm/L	 Recoat 4 hrs

Where to use	
Substrate :	White Set Plaster PVC and Timber
Interior :	Ceilings, Doors, Skirting and Architraves, Trims, Walls and Window Frames
Exterior :	Doors, Facias, Trims, Weatherboards, Walls and Window Frames
<p>Note: Suitable for sealing water-based and oil-based stains including; coffee, graffiti, marker pens, mould &amp; mildew, smoke and pet stains, rust stains, sap and tannin bleed, water stains.</p>	

Typical Properties	
Colour	White Undercoat
Application method	Brush, roller, spray, airless spray
Clean-up	Mineral Turpentine
Dry time - touch dry	45 minutes
Dry time - recoat	4 hours
Coverage	Up to 16 sqm/L dependent upon surface porosity, profile and method of application.
Sizes	1L, 2L, 4L, 10L
VOC	383 g/L
Volume solids	51%

Film build wet	62 µm
Film build dry	32 µm

### Precautions

- Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity, drying times will be extended.
- Do NOT apply if rain or dew is expected within 24 hours of application.
- Provide adequate ventilation during application and the drying period.
- Do NOT paint in direct sunlight.
- Soak all cloths with traces of paint or solvent in water to prevent spontaneous combustion.

### Surface Preparation

General surface preparation	<p>All surfaces must be clean, bare, dry and free of wax, grease and other surface contaminants. Fill any cracks, nail holes or imperfections with the appropriate filler. Sand smooth and dust down. If mould is present, treat the surface with a mould remover to effectively eliminate the mould spores. All traces of mould must be removed prior to painting.</p> <p>Some primers used on preprimed timber are of low quality. Unless a painting specification is supplied by the timber manufacturer, the timber must be sanded back to bare timber before coating.</p>
Previously painted surface	<p>Conduct an adhesion test [1], followed by a compatibility test [2]. Scrape all loose flaking paint. Sand surface smooth to a dull finish and remove all dust. Apply one coat of Haymes Ultralock or Ultracover to any patched areas followed by one coat over the entire surface.</p>
Timber	<p>Weathered or greyed timber should be sanded to the original timber surface. Apply one coat of Haymes Paint Ultralock for tannin-rich timbers. For pre-primed timbers, please refer to the manufacturer's painting specification [3].</p>
uPVC	<p>Wash surface with Haymes Paint Unikleen and rinse with clean water. Scuff the surface with sandpaper and remove dust.</p>
White Set plaster	<p>Plaster must have cured for 28 days, check surface integrity, moisture content and pH. Apply one coat of Haymes Paint Ultralock to the correctly prepared surface.</p>
Stain sealing	<p>Wash the surface thoroughly to remove as much stain as possible and allow to dry. Apply one coat of Haymes Ultralock and allow to dry overnight prior to top coating. Some stains may require two coats.</p>
Adhesion test	<p>[1] To check the adhesion of an existing coating, cut an 'X' lightly into the coating and firmly apply adhesive tape across the cut and then remove tape. If the tape removes the existing coating, remove all previous coatings before painting.</p>
Compatibility test	<p>[2] Test for compatibility with a previous coating by sanding and cleaning a small inconspicuous area. Apply 1 coat of the desired topcoat and allow to dry. After 24 hours, conduct an adhesion test. If the tape removes the coating, remove all previous coatings before painting. It is recommended to conduct the compatibility test in several areas.</p>
Preprimed timber	<p>[3] Some primers used on preprimed timber are of low quality. Unless a painting specification is supplied by the timber manufacturer, the timber must be sanded back to bare timber before coating.</p>

### Surface Preparation

**IMPORTANT:**

You must consult the installation guide of the construction product you are using for information on coatings and finishing guide to determine product suitability prior to commencing work. For further information and product specification consult a Haymes Paint representative on 1800 033 431.

### Application

- Stir thoroughly before and during application using a broad flat stirrer.
- Apply one to two coats.
- Application methods:
  - Brush: Use a quality synthetic brush.
  - Roller: Use a 8-10mm microfibre cover on smooth to semi smooth surfaces.
  - Spray: Airless Spray, High Volume Low Pressure (HVLP).

### Thinning

Thinning is not recommended unless spraying; add up to 100mL clean mineral turpentine per litre of product to achieve acceptable atomisation. Up to 50mL of mineral turpentine can be added per litre of product to ease application under very warm conditions.

### Care and Maintenance

Protect the surface against knocks and abrasion for 7 days. Maximum adhesion may take several days to develop depending on film build and drying conditions.

### Storage

Read the Safety Data Sheet (SDS) for this product for specific directions on storage (section 7 of the SDS) and transport (section 10 of the SDS). To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431. Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks. Ensure the container label remains legible for future identification and usage.

### Safety & First Aid

Read the Safety Data Sheet (SDS) for this product, prior to using this product. The SDS contains important information on how to use this product safely including hazards and precautions, personal protective equipment, storage and first aid in the event of an emergency. To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431.

If the product is swallowed, phone the Poisons Information Centre on 13 11 26 or contact a Doctor. Keep out of reach of children. Flammable liquid and vapour. Harmful if inhaled. May cause drowsiness or dizziness. Avoid breathing vapours. Only use this product in a well ventilated space and away from ignition sources. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

### Protect our Environment

Do NOT pour any leftover product down the drain. Retain in a marked, sealed container for future use or disposal via chemical waste collection programs such as Paintback®. Visit [www.paintback.com.au](http://www.paintback.com.au) for details of your nearest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

### Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Important safety information is available on the Safety Data Sheet available from Haymes Paint website [www.haymespaint.com.au](http://www.haymespaint.com.au). Further information about other Haymes products recommended to be used in conjunction with this product are available from the website in the form of Product Data Sheets in relation to those products. We are continually updating materials and methods, so please ensure you have the latest information on the Haymes Paint website.

### Disclaimer

The information provided in this Product Data Sheet is correct at the time of preparation, but is subject to change. It is your responsibility to check the Haymes Paint website at [www.haymespaint.com.au](http://www.haymespaint.com.au) to ensure that you have the most current Product Data Sheet. Product application and performance is affected by environmental conditions at the time of application and drying. Paint applied in conditions outside of what is recommended may dry more slowly or be less durable, or produce a less uniform appearance.

### Version

Version and Date Issued	Version 2.1 Date 13/07/2023
Supersedes	Version 2.0 Date 27/06/2022

Henry Haymes Pty Ltd  
A.B.N. 14 004 201 638  
Waringa Drive  
Wendouree Industrial Park  
Ballarat Vic 3355  
Freecall 1800 033 431  
[www.haymespaint.com.au](http://www.haymespaint.com.au)