



## GSA TOTAL JOINTING COMPOUND

### Description

A specially formulated total jointing compound for plasterboard or as a finishing coat when a base coat has been used. Also, can be used as a repair compound for fixing cracks and/or holes.

**Preparation:** If liquid has separated from the compound, re-mix prior to use. Clean tools before use & always replace lid.

### Application:

1. Apply GSA Jointing Tape along the joint and smooth by hand.
2. Using a 100mm broad knife, cover the tape with a thin layer of GSA Total Jointing Compound.
3. Allow 24 hours to dry, then, using a 150mm broad knife, follow with a second coat of GSA Total Jointing Compound, filling the recessed area until it is level with the face of the sheet. Allow to dry for 24 hours.
4. Using a 200mm broad knife, apply a final coat of the compound along the joint to a width of 250mm, leaving it slightly raised over the middle of the joint & feather the edges so they are smooth.
5. After approximately 24 hours drying time, joint can be sanded to a smooth finish with 150 grit sandpaper.

**Coverage:** 3 coats of GSA Total Jointing Compound requires 31kg per 180 square meters of plasterboard. Final coat only, 8kg per 100 square meters plasterboard

**Packaging:** TJC01 - 1kg, TJC05 - 5kg, TJC15 - 15kg

**Clean Up:** Clean up with water.

**Storage:** Replace lid tightly when not in use. Do not freeze. Store in a cool, dry place.

**First Aid:** Please refer to the Safety Data sheet which is available at [www.cwbrands.com.au/](http://www.cwbrands.com.au/)

### Disclaimer

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Products conform solely to the information contained in this and other related CW Brands Pty Ltd publications.

CW Brands Pty Ltd reserves the right to make changes to specifications and information related to the products at any time. Users are asked to check that the literature in their possession is the latest issue. Statements contained herein should not be considered as a warranty of any kind, expressed or implied in describing the performance or suitability of the product for a particular application. No liability is accepted for infringement of any patents or any other intellectual property right.

